

# 1187 Low Pressure Bellows Gauge

## FEATURES

- Inches of water ranges
- Available with diaphragm seals
- Bellows-actuated mechanism
- Easy adjustable micrometer pointer
- Solid front safety case with pressure relief back
- Brass, 316 stainless steel or Monel® wetted parts

## TYPICAL USES

- Oil & gas
- Chemical and petrochemical plants
- Water and wastewater pressure control
- Equipment skids
- Process and industrial applications



**1187**  
 4½" dial size

## SPECIFICATIONS

Accuracy:	2%-1%-2% (ASME B40.100 Grade A)
Dial Size:	4½"
Range:	10IW Vacuum to 10 psi
Process Connection Location:	Back
Process Connection Size:	¼ NPT Male, ½ NPT Male
Case Style:	Solid Front (dry only)
Movement:	416 Stainless steel
Window Material:	Glass (STD.), Shatter Proof Glass (OPT.)
Dial:	White Aluminum with Black Markings
Pointer:	Micrometer Adjustable
Weather Protection:	IP54
Dampening Options:	Throttle screw, dampeners, capillary, diaphragm seals and snubbers
Mounting:	Flush

## WETTED COMPONENTS

Bellows	Process Connection	Joints
Brass, 316 SS, Monel®	Brass, 316 SS, Monel®	Soldered: Brass Welded: 316 SS, Monel®

## NON-WETTED COMPONENTS

Case	Ring	Back Cover
Aluminum, Black Epoxy Coated	Hinged Steel, Black Epoxy Coated	Polypropylene

## KEY BENEFITS

- Highly sensitive system providing a safe means for measuring process media
- Ideal product solution for many installations
- Rugged design

## MIN/MAX TEMPERATURE LIMITS

Version	Ambient	Process	Storage
Dry	-20°F to 150°F (-29°C to 66°C)	-20°F to 150°F (-29°C to 66°C)	-40°F to 150°F (-40°C to 66°C)

## 1187 Low Pressure Bellows Gauge

ORDERING CODE	Example:	451187	S	S	02	B	XC4	10IW
<b>Dial Size/Model Code</b>								
451187 - 4½" aluminum case, solid front		451187						
<b>System (tube and process connection)</b>								
A - Brass bellows, brass process connection								
S - 316 Stainless steel bellows, stainless steel process connection			S					
P - K-Monel <sup>®</sup> 500 bellows, Monel <sup>®</sup> 400 process connection								
<b>Case Design</b>								
S - Solid front, Dry				S				
<b>Process Connection Sizes</b>								
02 - ¼ NPT Male					02			
04 - ½ NPT Male								
<b>Process Connection Location</b>								
B - Back mount connection						B		
<b>Options (If choosing an option(s) must include an "X")</b>								X__
C4 - Individual calibration chart (in accordance with ASME B40.100:2013. Accuracy traceable to N.I.S.T)							C4	
D3 - DuraVis™ Retroreflective Dial								
6B - Cleaned for gaseous, oxygen service								
F8 - Gauge, flexible line assembly and diaphragm seal								
PD - Acrylic window								
SG - Safety glass								
NG - Non-glare glass								
DA - Marking on dial								
NH - Stainless steel tag wired to case								
NN - Paper tag bonded to case								
<b>Range (coding examples only, see range table on page 3 for all standard ranges)</b>								
<b>Single Scales</b>								
10IW - 10" H <sub>2</sub> O								10IW

## 1187 Low Pressure Bellows Gauge

STANDARD PRESSURE RANGE							
	in. H <sub>2</sub> O	mmHg	in. Hg	mmH <sub>2</sub> O	psi	mbar	kPa
Vacuum	N10IW	N18MM	-	-	-	-	-
	N15IW	N28MM	-	-	-	-	-
	N20IW	N37MM	-	-	-	-	-
	N30IW	N56MM	-	-	-	-	-
	N40IW	N75MM	-	-	-	-	-
	N60IW	N110MM	-	-	-	-	-
	N80IW	N150MM	-	-	-	-	-
	N100IW	N180MM	-	-	-	-	-
	N150IW	N270MM	-	-	-	-	-
	-	-	N10IM	-	-	-	-
-	-	N15IM	-	-	-	-	-
-	-	N20IM	-	-	-	-	-
-	-	-	N125/125MW	-	N12.5/12.5MB	N1.25/1.25KP	-
-	N5/5IW	-	-	-	-	-	-
-	-	-	N200/200MW	-	N20/20MB	N2/2KP	-
-	N10/10IW	-	-	-	-	-	-
-	-	-	N300/300MW	-	N30/30MB	N3/3KP	-
-	-	-	N500/500MW	-	N50/50MB	N5/5KP	-
Compound	N30/10IW	-	-	-	-	-	-
	N20/20IW	-	-	-	-	-	-
	N10/30IW	-	-	-	-	-	-
	N30/30IW	-	-	-	-	-	-
	N40/20IW	-	-	N800/800MW	-	N80/80MB	N8/8KP
	-	-	N1250/1250MW	-	N125/125MB	N12.5/12.5KP	-
	N70/30IW	-	-	-	-	-	-
	-	-	N2000/2000MW	-	N200/200MB	N20/20KP	-
	-	-	N3000/3000MW	-	N300/300MB	N30/30KP	-
	-	5IW	-	-	-	-	-
Positive Pressure	10IW	-	-	25MW	-	25MB	2.5KP
	15IW	-	-	-	-	-	-
	-	-	-	400MW	-	-	-
	-	-	-	-	-	40MB	4KP
	20IW	-	-	-	-	-	-
	-	-	-	600MW	-	-	-
	-	-	-	-	-	60MB	6KP
	30IW	-	-	-	-	-	-
	-	-	-	1000MW	-	-	-
	40IW	-	-	-	-	100MB	10KP
	60IW	-	-	-	-	-	-
	-	-	-	1600MW	-	-	-
	-	-	-	-	-	160MB	16KP
	80IW	-	-	-	-	-	-
	-	-	-	2500MW	-	-	-
	100IW	-	-	-	-	250MB	25KP
	-	-	-	-	5#	-	-
	150IW	-	-	-	-	-	-
	-	-	-	4000MW	-	-	-
	-	-	-	-	-	400MB	40KP
-	-	-	-	8#	-	-	
-	-	-	6000MW	-	-	-	
-	-	-	-	-	600MB	60KP	
-	-	-	-	10#	-	-	

## 1187 Low Pressure Bellows Gauge

### DIMENSIONS in [ ] are millimeters

For reference only, consult Ashcroft for specific dimensional drawings

Dial Size Inches	A	B	E	F	H	I	K	M	S	U	CC	LL	Weight (lbs)
4 1/2	6 5/32 [155]	3 7/16 [87]	5 5/8 [137]	1 5/8 [40]	1 1/16 [40]	5/8 [16]	1 3/32 [28]	4 7/8 [124]	1 1/16 [17]	3/4 [19]	#10-24 24	1/16 - 1/4 [2] [6]	2.63 1.2 kg

